



CBM User's Guide

Helpful tips for using and programming your Commodore computer

Comet64 (V-1541) Command Reference

Note: in the examples below, anything noted in lower-case letters is to be replaced with your own specific information, like folder, disks, and program names.

Commands when using a single virtual drive (drive 0: when not specified)	
LOAD"@email@domain.com,password",2 or LOAD"@userid,password",2 or LOAD">LOGIN userid,password",2	Log-in to your CommodoreServer.com account using either your e-mail address or user I.D. Replace PASSWORD with the actual password for your account.
LOAD"! ",2 or LOAD">DISKS",2	List a directory of all disk images in the current active folder or on-line storage space.
LOAD"/folder",2 or LOAD">CF folder",2	Change the active folder to a different folder or sub-directory.
LOAD"/@userid",2	Change the active folder to a folder in one of your friend's shared account. To return to your own account use LOAD"/@",2.
LOAD"#filename.D64",2 or LOAD">INSERT filename.D64",2	Insert (a.k.a. mount) a disk image into the virtual drive.
LOAD"\$",2	List the contents of the mounted disk file.
LOAD"filename",2	Load a binary program from the mounted disk image into memory.
SAVE"filename",2	Save the binary program in memory to the mounted disk image.
LOAD">SCRATCH filename",2	Remove/delete a file from the mounted disk image.
LOAD"%",2 or LOAD">NAME",2	Display the filename of the mounted disk image.
LOAD">BLOCKS",2	Show the number of blocks free on the mounted disk image.
LOAD">REMOVE",2	Remove the currently mounted disk image.
LOAD">HELP",2	List the commands available for the V-1541 and their proper syntax.
LOAD">FIND text",2	Find the specified text contained in any file name in the disk images stored in your virtual drive account.
LOAD">MF folder",2	Make a new sub-folder in the currently active folder.

Commands when using a single virtual drive (drive 0: when not specified)	
LOAD">NEW diskfile, diskname, id",2	Create a new, formatted disk image on in the currently active folder. diskfile is the name of the new .D64 file, diskname is the 16 character name of the disk, and id is the 2 character disk I.D.
LOAD">LOGOUT",2	Logs you out of your account, but keeps you connected to the @Public drive.
LOAD">QUIT",2	Logs you out of your account and terminates your connection to CommodoreServer.

Commands when using multiple virtual disk drives	
The CommodoreServer V-1541 allows you to connect up to ten disk images at once, using disk identifiers of 0: through 9:. In the examples below, I will use virtual drives 0: and 1:, but using any of the drive numbers will work.	
LOAD">CF 0:folder",2	Change drive 0's active folder.
LOAD">DISKS 0:",2	List a disk directory of the folder attached to disk 0.
LOAD">INSERT 0:file.D64",2	Insert (a.k.a. mount) a disk image into virtual drive 0.
LOAD">\$ 0:",2	List the contents of the disk mounted to drive 0.
LOAD"0:filename",2	Load a binary program from the disk mounted in drive 0.
LOAD">COPY 0:filename, 1:",2	Copy a file from the disk mounted in drive 0 to the disk mounted in drive 1 .
LOAD">COPY 0:filename, 1:newfile",2	Copy a file from the disk mounted in drive 0 to drive 1, but give it a new name.
LOAD">COPY 0:filename, newfile",2	Copy a file on the disk mounted in drive 0 to a new file on drive 0.
LOAD">SCRATCH 0:filename",2	Remove/delete a file from the disk image mounted in drive 0.